


(Patented in Japan)

## Small Diaphragm Valve

### SMV series



### Features

Utilization of Shape Memory Alloy provides the following features:

- Compact size and light weight – 4 × 16 × 16.5mm (excluding contacts) and approximately 1g
- Silent, operating without the noise generated by solenoid-actuated valves.
- Slower opening-closing operation in comparison to solenoid valves. Suitable for applications sensitive to rapid fluid movement, such as fluid supply to chips used in microfluidic applications.
- Possible to actuate at low power consumption – 0.3 W or less.

Note: Details including specifications etc. may be changed at any time without notice

### TAKASAGO ELECTRIC, INC.

66 KAKITSUBATA, NARUMI-CHO, MIDORI-KU, NAGOYA, 458-8522 JAPAN

Tel +81-52-891-2301 Fax+81-52-891-7386

E-mail: [info@takasago-elec.co.jp](mailto:info@takasago-elec.co.jp) URL: <http://www.takasago-elec.com>

## Specifications

Type	2-Way N.C. *	
Orifice Diameter	0.4mm	
Operating Pressure Range	IN : 0 - 80kPa	
	OUT: 0 - 30kPa	
Fluid Temp. Range	5 - 40°C	
Ambient Temp. Range	5 - 40°C	
Current	250mA	
Operational frequency	MAX 0.5Hz	
Material	Body	PEEK or PPS
	Diaphragm gasket	Perfluoroelastomer or FPM
Dimensions	4X16X16.5mm	

\*Production of N.O. Type also possible

## Electrical supply

Current 250mA

Constant-current source recommended. Constant-current-providing circuit required.

## Dimensions

